

## Conlit Brandschutzsysteme

Abschottungssysteme: Rohrabschottungen von brennbaren und nichtbrennbaren Rohrleitungen R30 bis R90

### Conlit 150 U

Innen Durchmesser (mm)	Dämmdicke (mm)	Durchmesser Kernbohrung (mm)
10	25	60
12	24	60
14	23	60
15	22,5	60
16	22	60
17	21,5	60
18	21	60
20	20	60
21	19,5	60
22	19	60
25	17,5	60
26	17	60
27	16,5	60
28	26	80
32	24	80
34	23	80
35	22,5	80
40	20	80
42	19	80
42	29	100
48	26	100
50	25	100
53	23,5	100
54	38	130
58	36	130
60	35	130
63	33,5	130
64	33	130
64	58	180

Innen Durchmesser (mm)	Dämmdicke (mm)	Durchmesser Kernbohrung (mm)
75	52,5	180
76	37	150
76	52	180
78	36	150
83	33,5	150
89	30,5	150
89	65,5	220
90	65	220
102	39	180
108	36	180
108	71	250
110	35	180
110	70	250
113	68,5	250
114	33	180
114	68	250
133	43,5	220
135	42,5	220
140	40	220
140	70	280
159	30,5	220
160	30	220
169	40,5	250
169	78	325
210	40	
219	40	
274	40	
324	40	
326	40	